

	Type	L #	Hits	Search Text	DBs
1	BRS	L1	9413	dut or (device near2 under near2 test)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB
2	BRS	L2	56431	(input near2 port\$2) and (output near2 port\$2)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB
3	BRS	L3	12159 42	laser or (light near2 source) or led	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB
4	BRS	L4	20757 6	reference near2 (signal\$2 or beam\$2 or light)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB
5	BRS	L5	4645	(first near2 switch\$5) and (second near2 switch\$5) and (router\$2 or coupler)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB
6	BRS	L6	2	1 and 2 and 3 and 4 and 5 and @ad<=20020220	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB
7	BRS	L7	11	1 and 2 and 3 and 5 and @ad<=20020220	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB